



# CALORWATER D /20 120°C L/L ANTISTATIC

## LONG LENGTH HOT WATER HOSE



- ✓ Hot water & coolant hose
- ✓ Engine heating systems
- ✓ DIN 73411:79
- ✓ Antistatic construction

### APPLICATION

Delivery hose for hot water and coolant fluids with medium aggressiveness, used in engine cooling and heating systems. Also suitable for washdown applications.

### TUBE

Black, smooth, antistatic EPDM rubber compound

### REINFORCEMENT

High strength synthetic plies

### COVER

Black, smooth, cloth impression EPDM rubber compound, resistant to abrasion, ozone and weathering.

### KEY PERFORMANCE

<b>Temperature:</b>	-40°C to +120°C
<b>Range</b>	-40°F to +248°F
<b>Working Pressure:</b>	20 bar
<b>Bursting Pressure:</b>	60 bar

ID		OD		WEIGHT	WP		BP		BENDING RADIUS	COIL LENGTH
mm	inch	mm	inch		bar	psi	bar	psi		
8	5/16	15	19/32	0,17	20	300	60	900	40	MAX 100
10	3/8	17	43/64	0,20	20	300	60	900	75	MAX 100
10	3/8	19	3/4	0,22	20	300	60	900	80	MAX 100
13	1/2	20	25/32	0,28	20	300	60	900	105	MAX 50
15	19/32	23	29/32	0,38	20	300	60	900	115	MAX 50
16	5/8	23	29/32	0,36	20	300	60	900	120	MAX 50
19	3/4	27	1 1/16	0,44	20	300	60	900	140	MAX 50
25	1	36	1 11/32	0,78	20	300	60	900	200	MAX 50

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

### BRANDING

TGT CALORWATER W.P. 20 BAR D Ø ITALY

