



CALORAD D /3

RADIATOR HOSE



- ✓ Radiator hose
- ✓ Engine cooling systems
- ✓ Hot water & coolant
- ✓ EPDM rubber construction

APPLICATION

Delivery hose for hot water and coolant fluids, used in engine cooling and heating systems. Suitable for radiator hose applications.

TUBE

Black, smooth, EPDM rubber compound

REINFORCEMENT

High strength synthetic plies

COVER

Black, smooth, cloth impression EPDM rubber compound, resistant to abrasion, ozone and weathering.

KEY PERFORMANCE

Temperature: -40°C to +120°C
Range -40°F to +248°F

Working Pressure: 3 bar

Bursting Pressure: 10 bar

ID		OD		WEIGHT	WP		BP		COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	m
13	1/2	19	3/4	0,20	3	45	10	150	1/40
16	5/8	22	7/8	0,25	3	45	10	150	1/40
18	45/64	24	61/64	0,28	3	45	10	150	1/40
20	25/32	26	11/32	0,30	3	45	10	150	1/40/61
22	7/8	28	17/64	0,32	3	45	10	150	1/40/61
25	1	32	11/4	0,42	3	45	10	150	1/40/61
28	17/64	36	127/64	0,47	3	45	10	150	1/40/61
30	13/16	38	11/2	0,53	3	45	10	150	1/40/61
32	1 1/4	40	137/64	0,57	3	45	10	150	1/40/61
35	13/8	43	145/64	0,61	3	45	10	150	1/40/61
38	1 1/2	47	127/32	0,75	3	45	10	150	1/40/61
40	137/64	49	115/16	0,86	3	45	10	150	1/40/61
42	1 21/32	51	2	0,90	3	45	10	150	1/40/61
45	1 25/32	54	2 1/8	0,92	3	45	10	150	1/40/61
48	1 57/64	58	2 9/32	1,04	3	45	10	150	1/40/61
51	2	61	2 13/32	1,10	3	45	10	150	1/40/61
55	2 11/64	65	2 9/16	1,18	3	45	10	150	1/40/61
60	2 23/64	70	2 3/4	1,28	3	45	10	150	1/40/61
65	2 9/16	75	2 61/64	1,37	3	45	10	150	1/40/61
70	2 3/4	80	3 5/32	1,47	3	45	10	150	1/40/61
76	3	86	3 25/64	1,59	3	45	10	150	1/40/61
80	3 5/32	92	3 5/8	1,90	3	45	10	150	1/40/61
90	3 35/64	102	4	2,15	3	45	10	150	1/40/61
102	4	113	4 29/64	2,35	3	45	10	150	1/40/61
110	4 21/64	123	4 27/32	2,50	3	45	10	150	1/40/61

BRANDING

TGT CALORAD D W.P. 3 BAR ITALY



CALORAD



W.P. 3 BAR



ITALY



sales@ifpp.co.uk



www.ifpp.co.uk