



# CALORDIN

## RADIATOR HOSE DIN 73411:79



- ✓ Radiator & coolant transfer
- ✓ Engine cooling systems
- ✓ DIN 73411:79
- ✓ EPDM rubber construction

### APPLICATION

Delivery hose for hot water and coolant fluids, used in engine cooling and heating systems. Suitable for radiator hose applications.

### TUBE

Black, smooth, EPDM rubber compound

### REINFORCEMENT

High strength synthetic plies

### COVER

Black, smooth, cloth impression EPDM rubber compound, abrasion, ozone and weather resistant

### KEY PERFORMANCE

**Temperature:** -40°C to +120°C  
**Range** -40°F to +248°F

**Working Pressure:** 4 bar

**Bursting Pressure:** 12 bar

ID		OD		WEIGHT	WP		BP		COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	m
18	45/64	25	1	0,30	4	60	12	180	1/40
20	25/32	27	1 1/16	0,32	4	60	12	180	1/40/61
22	7/8	29	1 9/64	0,35	4	60	12	180	1/40/61
25	1	33	1 19/64	0,42	4	60	12	180	1/40/61
28	1 7/64	36	1 27/64	0,47	4	60	12	180	1/40/61
30	1 3/16	38	1 1/2	0,53	4	60	12	180	1/40/61
32	1 1/4	40	1 37/64	0,57	4	60	12	180	1/40/61
35	1 3/8	43	1 45/64	0,61	4	60	12	180	1/40/61
38	1 1/2	47	1 27/32	0,75	4	60	12	180	1/40/61
40	1 37/64	50	1 31/32	0,88	4	60	12	180	1/40/61
42	1 21/32	52	2 3/64	0,92	4	60	12	180	1/40/61
45	1 25/32	55	2 11/64	0,98	4	60	12	180	1/40/61
48	1 57/64	58	2 9/32	1,04	4	60	12	180	1/40/61
51	2	61	2 13/32	1,10	4	60	12	180	1/40/61
55	2 5/32	65	2 9/16	1,18	4	60	12	180	1/40/61
60	2 23/64	70	2 3/4	1,28	4	60	12	180	1/40/61
65	2 9/16	75	2 61/64	1,37	4	60	12	180	1/40/61
70	2 3/4	80	3 5/32	1,47	4	60	12	180	1/40/61
76	3	86	3 25/64	1,59	4	60	12	180	1/40/61
80	3 5/32	92	3 5/8	1,90	4	60	12	180	1/40/61
90	3 35/64	102	4	2,15	4	60	12	180	1/40/61
102	4	114	4 31/64	2,54	4	60	12	180	1/40/61
110	4 21/64	124	4 7/8	2,65	4	60	12	180	1/40/61

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

### BRANDING



sales@ifpp.co.uk



www.ifpp.co.uk