



CALORGEN D /10 120°C

HOT WATER HOSE



- ✓ Hot water & low-pressure steam
- ✓ Low-pressure washer machines
- ✓ EPDM rubber construction
- ✓ General industrial use

APPLICATION

Delivery hose for hot water mixed with steam (not saturated). Very good for low-pressure washer machines.

TUBE

Black, smooth, EPDM rubber compound

REINFORCEMENT

High strength synthetic plies

COVER

Black, smooth, cloth impression EPDM rubber compound, resistant to abrasion, ozone and weathering.

KEY PERFORMANCE

Temperature: -40°C to +120°C
Range -40°F to +248°F

Working Pressure: 10 bar

Bursting Pressure: 30 bar

ID		OD		WEIGHT	WP		BP		COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	m
10	13/32	20	23/32	0,29	10	150	30	450	40
12	15/32	22	7/8	0,33	10	150	30	450	40
13	1/2	23	29/32	0,35	10	150	30	450	40
15	19/32	25	1	0,39	10	150	30	450	40
16	5/8	26	11/32	0,42	10	150	30	450	40
18	45/64	28	17/64	0,45	10	150	30	450	40
19	3/4	29	19/64	0,47	10	150	30	450	40/61
20	25/32	30	1 3/16	0,49	10	150	30	450	40/61
25	1	35	1 3/8	0,59	10	150	30	450	40/61
30	1 3/16	41	1 5/8	0,85	10	150	30	450	40/61
32	1 1/4	42	1 21/32	0,88	10	150	30	450	40/61
32	1 1/4	44	1 47/64	0,90	10	150	30	450	40/61
35	1 3/8	47	1 27/32	0,97	10	150	30	450	40/61
38	1 1/2	50	1 31/32	1,22	10	150	30	450	40/61
40	1 37/64	54	2 1/8	1,33	10	150	30	450	40/61
42	1 21/32	54	2 1/8	1,41	10	150	30	450	40/61
45	1 25/32	61	2 13/32	1,67	10	150	30	450	40/61
51	2	67	2 41/64	1,85	10	150	30	450	40/61
60	2 23/64	75	2 61/64	3,07	10	150	30	450	40/61
60	2 23/64	82	3 15/64	3,54	10	150	30	450	40/61

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

BRANDING

