



AERGEN D 20 L/L

COMPRESSED AIR LONG LENGTH HOSE



- ✓ Compressed air delivery
- ✓ For inert fluids
- ✓ Long-length construction
- ✓ SBR/EPDM cover

APPLICATION

Delivery hose for compressed air and inert fluids

TUBE

Black, smooth, SBR rubber compound

REINFORCEMENT

High strength synthetic plies

COVER

Black, smooth, SBR/EPDM rubber compound, abrasion and weather resistant

KEY PERFORMANCE

Temperature: -30°C to +80°C
Range -22°F to +176°F

Working Pressure: 20 bar

Bursting Pressure: 60 bar

ID		OD		WEIGHT kg/m	WP		BP		BENDING RADIUS mm	COIL LENGTH m
mm	inch	mm	inch		bar	psi	bar	psi		
6	1/4	14	35/64	0.18	20	300	60	900	50	MAX 100
8	5/16	17	43/64	0.25	20	300	60	900	65	MAX 100
10	3/8	19	3/4	0.29	20	300	60	900	80	MAX 100
13	1/2	23	29/32	0.40	20	300	60	900	105	MAX 50
15	19/32	25	1	0.46	20	300	60	900	120	MAX 50
16	5/8	26	1 5/16	0.48	20	300	60	900	130	MAX 50
19	3/4	30	1 3/16	0.62	20	300	60	900	150	MAX 50
25	1	37	1 29/64	0.86	20	300	60	900	200	MAX 50

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

BRANDING

TGT AERGEN W.P. 20 BAR D ITALY

