



AERDEL D /40 160°C

HIGH TEMPERATURE COMPRESSED AIR HOSE



- ✓ High-temperature air delivery
- ✓ For dry air only
- ✓ Heavy-duty pneumatic tools
- ✓ Heat-resistant rubber compound

APPLICATION

Delivery hose for high temperature compressed air suitable for heavy duty pneumatic tools in road constructions, railways works, tunneling and mining, etc. Recommended for use with dry air only

TUBE

Black, smooth, EPM rubber compound

REINFORCEMENT

High strength synthetic plies

COVER

Black, smooth, cloth impression EPDM rubber compound, abrasion and weather resistant

KEY PERFORMANCE

Temperature:	-30°C to +160°C
Range	-22°F to +320°F
Working Pressure:	40 bar
Bursting Pressure:	120 bar

ID		OD		WEIGHT	WP		BP		BENDING RADIUS	COIL LENGTH
mm	inch	mm	inch		bar	psi	bar	psi		
51	2	70	2 3/4	1.93	40	600	120	1800	500	60
76	3	100	3 15/16	3.75	40	600	120	1800	740	60
102	4	128	5 15/32	5.12	40	600	120	1800	970	60

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

BRANDING

