



ABRASAND D /12

RADIATOR HOSE HELIX GROOVED



- ✓ Sand & abrasive blasting hose
- ✓ Industrial blasting systems
- ✓ ISO 4649 50 ± 5 mm³
- ✓ Suitable for compressor-fed blasting

APPLICATION

Delivery hose for sand and bead blasting applications.

TUBE

Black, smooth, NR/SBR conductive (R≤106 Ohm) rubber compound

REINFORCEMENT

High strength synthetic plies

COVER

Black, smooth, antistatic cloth impression SBR/NR rubber compound, resistant to abrasion and weathering.

KEY PERFORMANCE

Temperature: -40°C to +70°C
Range -40°F to +158°F

Working Pressure: 12 bar

Bursting Pressure: 36 bar

ID		OD		WEIGHT	WP		BP		COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	m
13	1/2	25	1	0,44	12	180	36	460	40
16	5/8	30	1 3/16	0,59	12	180	36	460	40
19	3/4	33	1 19/64	0,66	12	180	36	460	40/61
25	1	40	1 37/64	0,88	12	180	36	460	40/61
30	1 3/16	45	1 25/32	1,02	12	180	36	460	40/61
32	1 1/4	48	1 57/64	1,16	12	180	36	460	40/61
38	1 1/2	54	2 1/8	1,33	12	180	36	460	40/61
40	1 37/64	60	2 23/64	1,83	12	180	36	460	40/61
51	2	71	2 51/64	2,20	12	180	36	460	40/61
60	2 23/64	80	3 5/32	2,53	12	180	36	460	40/61
65	2 9/16	85	3 3/8	2,76	12	180	36	460	40/61
80	3 5/32	105	4 3/32	4,18	12	180	36	460	40/61
90	3 35/64	115	4 17/32	4,63	12	180	36	460	40/61
102	4	127	5	5,17	12	180	36	460	40/61

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

BRANDING

