



ABRASAND HD /18

SANDBLASTING HEAVY DUTY HOSE



- ✓ Heavy-duty abrasive blasting hose
- ✓ Increased wall thickness for longer life
- ✓ ISO 4649 50 ± 5 mm³
- ✓ Industrial blasting environments

APPLICATION

Delivery hose for sand and bead blasting applications, designed for high-pressure use and high abrasion resistance.

TUBE

Black, smooth, NR/SBR conductive (R≤106 Ohm) rubber compound

REINFORCEMENT

High strength synthetic plies

COVER

Black, smooth, antistatic cloth impression SBR/NR rubber compound, resistant to abrasion and weathering.

KEY PERFORMANCE

Temperature: -40°C to +70°C
Range -40°F to +158°F

Working Pressure: 18 bar

Bursting Pressure: 54 bar

ID		OD		WEIGHT	WP		BP		COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	m
13	1/2	25	1	0,45	18	270	54	810	40
16	5/8	30	1 3/16	0,63	18	270	54	810	40
19	3/4	30	1 5/16	0,53	18	270	54	810	40/61
19	3/4	33	1 19/64	0,71	18	270	54	810	40/61
25	1	40	1 37/64	0,96	18	270	54	810	40/61
30	1 3/16	45	1 25/32	1,10	18	270	54	810	40/61
32	1 1/4	48	1 57/64	1,26	18	270	54	810	40/61
35	1 3/8	54	2 1/8	1,66	18	270	54	810	40/61
38	1 1/2	54	2 1/8	1,44	18	270	54	810	40/61
40	1 9/16	60	2 23/64	1,96	18	270	54	810	40/61
51	2	71	2 51/64	2,39	18	270	54	810	40/61
60	2 3/8	80	3 5/32	2,75	18	270	54	810	40/61
65	2 9/16	85	3 3/8	2,78	18	270	54	810	40/61

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

BRANDING



sales@ifpp.co.uk



www.ifpp.co.uk