



ABRASTAR /12 HD36

SANDBLASTING HEAVY DUTY HOSE



- ✓ Professional abrasive blasting hose
- ✓ High abrasion resistance
- ✓ ISO 4649 36 ± 5 mm³
- ✓ For industrial surface preparation

APPLICATION

Delivery hose for sand and bead blasting applications, designed for high-pressure use and high abrasion resistance.

TUBE

Black, smooth, NR/SBR conductive (R≤106 Ohm) rubber compound

REINFORCEMENT

High strength synthetic plies

COVER

Black, smooth, antistatic cloth impression SBR/NR rubber compound, resistant to abrasion and weathering.

KEY PERFORMANCE

Temperature: -40°C to +70°C
Range -40°F to +158°F

Working Pressure: 12 bar

Bursting Pressure: 36 bar

ID		OD		WEIGHT	WP		BP		COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	m
13	1/2	27	1 1/16	0,44	12	180	36	540	40
16	5/8	30	1 3/16	0,59	12	180	36	540	40
19	3/4	33	1 19/64	0,71	12	180	36	540	40
25	1	40	1 37/64	0,96	12	180	36	540	40
30	1 3/16	45	1 25/32	1,00	12	180	36	540	40
32	1 1/4	48	1 57/64	1,26	12	180	36	540	40
38	1 1/2	56	2 13/64	1,44	12	180	36	540	40
40	1 37/64	60	2 23/64	1,65	12	180	36	540	40
51	2	71	2 51/64	2,39	12	180	36	540	40
60	2 23/64	80	3 5/32	2,50	12	180	36	540	40
65	2 9/16	85	3 3/8	2,72	12	180	36	540	40

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

BRANDING

