



ABRAPLUS D /40

PLASTER HOSE



- ✓ Mortar & plaster pumping hose
- ✓ Smooth bore for material flow
- ✓ ISO 4649 70 ± 5 mm³
- ✓ For medium-pressure pumps

APPLICATION

Plaster hose for mortar and rendering applications.

TUBE

Black, smooth, NR/SBR conductive rubber compound (R≤10⁶ Ohm)

REINFORCEMENT

High strength synthetic plies

COVER

Black, smooth, antistatic cloth impression SBR/NR rubber compound, resistant to abrasion and weathering.

KEY PERFORMANCE

Temperature:	-40°C to +70°C
Range	-40°F to +158°F
Working Pressure:	40 bar
Bursting Pressure:	120 bar

ID		OD		WEIGHT	WP		BP		BENDING RADIUS	COIL LENGTH
mm	inch	mm	inch		kg/m	bar	psi	bar		
25	1	37	1 29/64	0,73	40	600	120	1800	105	40/61
32	1 1/4	46	1 13/16	1,07	40	600	120	1800	118	40/61
35	1 3/8	50	1 31/32	1,23	40	600	120	1800	120	40/61
38	1 1/2	53	2 3/32	1,44	40	600	120	1800	125	40/61
40	1 9/16	56	2 13/64	1,52	40	600	120	1800	168	40/61
42	1 21/32	58	2 9/32	1,30	40	600	120	1800	175	40/61
51	2	68	2 11/16	1,99	40	600	120	1800	200	40/61
60	2 23/64	80	3 5/32	2,40	40	600	120	1800	260	40/61
65	2 9/16	85	3 3/8	2,90	40	600	120	1800	230	40/61
76	3	95	3 47/64	3,19	40	600	120	1800	250	40/61
80	3 5/32	105	4 9/64	3,53	40	600	120	1800	275	40/61
90	3 35/64	115	4 17/32	3,93	40	600	120	1800	300	40/61
102	4	127	5	4,50	40	600	120	1800	320	40/61

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

BRANDING

