



ABRACEM D /10

CEMENT DELIVERY HOSE



- ✓ Dry cement & powder transfer hose
- ✓ Designed for silo & bulk handling
- ✓ ISO 4649 70 ± 5 mm³
- ✓ Industrial dry material transfer

APPLICATION

Delivery hose for concrete, sand, gravel and general abrasive dry materials

TUBE

Black, smooth, NR/SBR conductive ($R \leq 10^6$ Ohm) rubber compound

REINFORCEMENT

High strength synthetic plies

COVER

Black, smooth, antistatic cloth impression SBR/NR rubber compound, resistant to abrasion and weathering.

KEY PERFORMANCE

Temperature: -40°C to +70°C
Range -40°F to +158°F

Working Pressure: 10 bar

Bursting Pressure: 30 bar

ID		OD		WEIGHT	WP		BP		COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	m
51	2	65	2 9/16	1.61	10	150	30	450	40/61
60	2 23/64	74	2 59/64	1.87	10	150	30	450	40/61
70	2 3/4	84	3 5/16	2.18	10	150	30	450	40/61
76	3	86	3 25/64	1.62	10	150	30	450	40/61
76	3	92	3 5/8	2.63	10	150	30	450	40/61
80	3 5/32	90	3 35/64	1.90	10	150	30	450	40/61
80	3 5/32	96	3 25/32	2.34	10	150	30	450	40/61
90	3 35/64	100	3 15/16	2.00	10	150	30	450	40/61
90	3 35/64	106	4 11/64	2.87	10	150	30	450	40/61
102	4	112	4 13/32	2.12	10	150	30	450	40/61
102	4	118	4 41/64	3.65	10	150	30	450	40/61
120	4 23/32	138	5 7/16	4.67	10	150	30	450	40/61

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

BRANDING

