



ABRAFLAT D /4

LAYFLAT CEMENT HOSE



- ✓ Layflat bulk material hose
- ✓ Compact storage when depressurised
- ✓ ISO 4649 70 ± 5 mm³
- ✓ Temporary material transfer

APPLICATION

Layflat delivery hose for concrete, sand, gravel and general abrasive dry materials

TUBE

Black, smooth, NR/SBR conductive ($R \leq 10^6$ Ohm) rubber compound

REINFORCEMENT

High strength synthetic plies

COVER

Black, smooth, antistatic cloth impression SBR/NR rubber compound, resistant to abrasion and weathering.

KEY PERFORMANCE

Temperature: -40°C to +70°C
Range -40°F to +158°F

Working Pressure: 4 bar

Bursting Pressure: 12 bar

ID		OD		WEIGHT	WP		BP		COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	m
90	3 35/64	100	3 15/16	2.00	4	60	12	180	40/61
102	4	112	4 13/32	2.25	4	60	12	180	40/61
110	4 21/64	120	4 23/32	2.40	4	60	12	180	40/61
127	5	137	5 25/64	2.77	4	60	12	180	40/61
152	6	162	6 3/8	3.30	4	60	12	180	40/61

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

BRANDING

