



ABRAPARA DualColor

NR RUBBER TUBING FOR ABRASIVE MATERIALS - NO PRESSURE



- ✓ Dual-colour wear indicator
- ✓ Abrasion-resistant NR tube
- ✓ For bulk material flow
- ✓ Lightweight flexible construction

APPLICATION

Gravity discharge hose for silos and hoppers, for abrasive materials such as sand, gravel and cement.

TUBE

Brown, smooth NR rubber compound, SHORE A 45

COVER

Black, smooth cloth impression NR rubber compound, SHORE A 45

KEY PERFORMANCE

| | |
|------------------------|-----------------|
| Temperature: | -40°C to +70°C |
| Range | -40°F to +158°F |
| Service Type: | No pressure |
| Suitable Media: | Abrasive solids |

| ID | | OD | | WEIGHT | COIL LENGTH |
|-----|----------|-----|----------|--------|-------------|
| mm | inch | mm | inch | kg/m | m |
| 80 | 3 5/32 | 90 | 3 35/64 | 1.45 | 5 |
| 90 | 3 35/64 | 100 | 3 15/16 | 1.63 | 5 |
| 102 | 4 | 112 | 4 13/32 | 1.83 | 5 |
| 110 | 4 21/64 | 120 | 4 23/32 | 1.97 | 5 |
| 120 | 4 23/32 | 130 | 5 1/8 | 2.14 | 5 |
| 127 | 5 | 137 | 5 25/64 | 2.26 | 5 |
| 130 | 5 1/8 | 140 | 5 33/64 | 2.31 | 5 |
| 140 | 5 33/64 | 150 | 5 29/32 | 2.48 | 5 |
| 152 | 6 | 162 | 6 3/8 | 2.69 | 5 |
| 160 | 6 19/64 | 170 | 6 11/16 | 2.82 | 5 |
| 168 | 6 39/64 | 178 | 7 | 2.96 | 5 |
| 180 | 7 15/16 | 190 | 7 31/64 | 3.17 | 5 |
| 193 | 7 19/32 | 203 | 8 | 3.34 | 5 |
| 203 | 8 | 211 | 8 5/16 | 3.50 | 5 |
| 203 | 8 | 213 | 8 25/64 | 3.56 | 5 |
| 220 | 8 21/32 | 228 | 8 31/32 | 3.75 | 5 |
| 220 | 8 21/32 | 230 | 9 5/8 | 3.85 | 5 |
| 254 | 10 | 262 | 10 5/16 | 4.35 | 5 |
| 254 | 10 | 264 | 10 25/64 | 4.45 | 5 |
| 273 | 10 3/4 | 281 | 11 5/8 | 4.50 | 5 |
| 273 | 10 3/4 | 283 | 11 9/64 | 4.76 | 5 |
| 280 | 11 5/16 | 290 | 11 27/64 | 4.88 | 5 |
| 305 | 12 | 315 | 12 13/32 | 5.31 | 5 |
| 320 | 12 19/32 | 330 | 12 63/64 | 5.56 | 5 |
| 350 | 13 25/32 | 360 | 14 11/64 | 6.10 | 5 |
| 400 | 15 3/4 | 410 | 16 9/64 | 7.00 | 5 |
| 450 | 17 23/32 | 460 | 18 1/8 | 7.79 | 5 |
| 500 | 19 11/16 | 510 | 20 25/32 | 8.64 | 5 |
| 600 | 23 5/8 | 610 | 24 5/32 | 10.35 | 5 |

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

